

FORMWORK 2.0

Brights / Neutrals



Construction	Tufted, Level Loop Pile
Face Fibre	Universal® Fibres solution-dyed Type 6 6 Nylon
Finished Face Weight	590 g/m ²
Gauge	40.5 / 10 cm
Rows	52 / 10 cm
Tuft Density	210,000 /m ²
Finished Pile Height	3.0 mm
Standard Backing	Comfort Lite 90% Recycled content Polyurethane Available with TractionBack® on request
Nominal Total Thickness	8.3 mm
Nominal Total Weight	3770 g/m ²
Plank Size	25 cm x 100 cm
Planks per Box	12 (3m ²)
Tile Size	50 cm x 50 cm
Tiles per Box	22 (5.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	29 dB
Sound Absorption (ISO354)	0.25 Class E
Alpha s values	125Hz 0.01, 250Hz 0.02, 500Hz 0.28, 1000Hz 0.24, 2000Hz 0.25, 4000Hz 0.37

ENVIRONMENTAL

90% Recycled content cushion backing

20% Recycled content yarn

13% Recycled content by total product weight

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

EPD verified - BRE certified

WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

INSTALLATION

Monolithic	Ashlar Random	Herringbone

CE MARKING

DOP: 0238/100402 EN 14041:2004					