

# NORDIC STORIES

Isograr

Construction	Tufted, Textured Loop Pile
Face Fibre	Solution dyed Type 6 6 Nylon
Finished Face Weight	575 g/m <sup>2</sup>
Gauge	47.2 / 10 cm
Rows	42 / 10 cm
Tuft Density	198,200 /m <sup>2</sup>
Finished Pile Height	2.0 - 4.5 mm
Standard Backing	Comfort Lite 90% Recycled content Polyurethane Available with TractionBack® on request
Nominal Total Thickness	8.9 mm
Nominal Total Weight	3860 g/m <sup>2</sup>
Plank Size	25 cm x 100 cm
Planks per Box	12 (3m <sup>2</sup> )
Tile Size	50 cm x 50 cm
Tiles per Box	20 (5m <sup>2</sup> )

## PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	31 dB
Sound Absorption (ISO354)	0.25 (H) Class E
Alpha s values	125Hz 0.01, 250Hz 0.06, 500Hz 0.58, 1000Hz 0.22, 2000Hz 0.28, 4000Hz 0.39

## ENVIRONMENTAL

90% Recycled content cushion backing

20% Recycled content yarn

17% Recycled content by total product weight

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT &amp; CRI Green Label Plus certified for indoor air quality

EPD verified - BRE certified

## WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

## CERTIFICATIONS


## INSTALLATION

Half Drop	Ashlar Random	Herringbone

## CE MARKING

--	--	--	--	--	--	--