

# TRACING LANDSCAPES

Geography Lesson / Map Reading

Construction	Tufted, Textured Tip Shear
Face Fibre	Econyl 100% Solution Dyed Nylon 6
Soil Release	StainSmart® for soil release, liquid repellence - selected colours only (see below)*
Finished Face Weight	570 - 600 g/m <sup>2</sup>
Gauge	47.2 / 10 cm
Rows	44 / 10 cm
Tuft Density	207,680 /m <sup>2</sup>
Finished Pile Height	2.9 mm
Standard Backing	Comfort Lite 90% Recycled Open Cell Polyurethane Available with TractionBack® on request
Nominal Total Thickness	9.4 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4125 g/m <sup>2</sup>
Tiles per Box	20 (5m <sup>2</sup> )

## PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	33 dB
Sound Absorption (ISO354)	0.30 (H) Class D
Alpha s values	125Hz 0.00, 250Hz 0.05, 500Hz 0.30, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.35

## ENVIRONMENTAL

26% Recycled content by total product weight

90% Recycled content cushion backing

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

## WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee


Latent Defects guarantee

### \*StainSmart® Applied to the following colours only

Etched Valley - High Cliffs - Wind Vane - Misty Mornings,  
Silver Lakes - Grey Moss

## CERTIFICATIONS


## INSTALLATION



## CE MARKING

--	--	--	--	--	--