

TRACING LANDSCAPES



Field Study

Construction	Tufted, Textured Loop Pile
Face Fibre	Econyl 100% Solution Dyed Nylon 6
Soil Release	StainSmart® for soil release, liquid repellence - selected colours only (see below)*
Finished Face Weight	560 g/m ²
Gauge	47.2 / 10 cm
Rows	44 / 10 cm
Tuft Density	207,680 /m ²
Finished Pile Height	3.6 mm
Standard Backing	Comfort Lite 90% Recycled Open Cell Polyurethane Available with TractionBack® on request
Nominal Total Thickness	9.4 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4100 g/m ²
Tiles per Box	20 (5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	33 dB
Sound Absorption (ISO354)	0.30 (H) Class D
Alpha s values	125Hz 0.00, 250Hz 0.05, 500Hz 0.30, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.35

ENVIRONMENTAL

- 26% Recycled content by total product weight
- 90% Recycled content cushion backing
- Manufactured in ISO14001 certified location using electricity from renewable sources
- GuT & CRI Green Label Plus certified for indoor air quality

WARRANTIES

- 12 year wear warranty
- Lifetime Antistatic guarantee
- Latent Defects guarantee

*StainSmart® Applied to the following colours only

Etched Valley - High Cliffs - Wind Vane - Misty Mornings, Silver Lakes - Grey Moss

CERTIFICATIONS

INSTALLATION



CE MARKING

--	--	--	--	--	--