

FORMWORK 2.0 Function Plus™



Brights / Neutrals

Construction	Tufted, Level Loop Pile
Face Fibre	Solution Dyed Nylon 6 6 (20% recycled content)
Soil Release	StainSmart® for soil release, liquid repellence (on light colours LRV >20)
Finished Face Weight	590 g/m ²
Gauge	39.4 / 10 cm
Rows	52 / 10 cm
Tuft Density	205,000 /m ²
Finished Pile Height	3.0 mm
Standard Backing	Function Plus™ Polymer modified bitumen hard back
Nominal Total Thickness	5.4 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	3700 g/m ²
Tiles per Box	20 (5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	25 dB
Sound Absorption (ISO354)	0.15 (H) Class E
Alpha s values	125Hz 0.01, 250Hz 0.02, 500Hz 0.05, 1000Hz 0.13, 2000Hz 0.30, 4000Hz 0.36

ENVIRONMENTAL

54% recycled content by total product weight

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

WARRANTIES

10 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

INSTALLATION



CE MARKING

--	--	--	--	--	--