

QUADRUS

Comet / Galaxy / Star



Construction	Twisted and heat set dual fibres - multi and monofilaments
Face Fibre	ECONYL® Type 6 nylon made with 100% regenerated nylon
Manufacturing Method	Manufacturing Method Tufted cut pile on non-woven polyester primary backing
Finished Face Weight	980 g/m ² approx
Pile Thickness	6.4 mm approx
Backing Type	Comfort Lite 90% Recycled content Polyurethane cushion Available with TractionBack® on request
Backing Thickness	6 mm approx
Total Thickness (ISO 1765)	12 mm approx
Tile Size	50 cm x 50 cm
Total Weight (ISO 8543)	4500 g/m ² (+/- 5% approx)
Tiles per Box	16 (4m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Cfl - s1
Fastness to Rubbing (EN ISO 105/X12)	4.5
Light Fastness (EN ISO 105/B01)	>6
Water Fastness (EN ISO 105/E01)	4.5
Shampoo Fastness (BS 1006)	4.5
Pile Density (ISO 8543)	0.129 g/cm ³
Comfort Class (EN 1307)	LC4
Heat Transmission Resistance (ISO 8302)	0.12 m ² K/W (Suitable for heated floors)
Use Classification (EN1307)	Class 32 Suitable for commercial contract use
Static Electricity (ISO 6356)	≤ 2.0 KV, Permanent Conductive Fibre

ENVIRONMENTAL

- 100% regenerated content yarn
- 33% Recycled content by total product weight (13% post consumer)
90% recycled Polyurethane
- Manufactured in ISO14001 certified location using electricity from renewable sources
- CRI Green Label Plus certified for indoor air quality

WARRANTIES

- 1 year guarantee against manufacturing defects
- 5 year wear guarantee according to manufacturers' recommendations re. installation and maintenance
- REACH 1907/2006/CE
This product is in conformance with REACH
- ADA / BS 8300 ISO 21542 Compliant

CERTIFICATIONS

INSTALLATION

<p>Monolithic</p>	<p>Quarter Turn</p>
-------------------	---------------------

CE MARKING

--	--	--	--	--	--	--