

CLERKENWELL

Design Quarter / EC1 / Finsbury Square



Construction	Tufted, Textured Tip Shear
Face Fibre	Solution Dyed Nylon 6 6 (20% recycled content)
Soil Release	StainSmart® for soil release, liquid repellence (on light colours LRV >20)
Finished Face Weight	720 g/m ² Design Quarter / 675 g/m ² EC1 / 840 g/m ² Finsbury Square
Gauge	47.2 / 10 cm
Rows	41.2 / 10 cm
Tuft Density	194,500 /m ²
Finished Pile Height	3.3 mm
Standard Backing	Comfort Plus® 90% recycled open cell polyurethane cushion backing Available with TractionBack® on request
Nominal Total Thickness	10.6 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4400 g/m ²
Tiles per Box	18 (4.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	34 dB
Sound Absorption (ISO354)	0.30 (H) Class D
Alpha s values	125Hz 0.03, 250Hz 0.08, 500Hz 0.54, 1000Hz 0.26, 2000Hz 0.32, 4000Hz 0.45

ENVIRONMENTAL

- 58% recycled content by total product weight
- Manufactured in ISO14001 certified location using renewable sources
- GuT & CRI Green Label Plus certified for indoor air quality
- EPD verified - BRE certified

WARRANTIES

- 15 year wear warranty
- Lifetime Antistatic guarantee
- Latent Defects guarantee

CERTIFICATIONS

INSTALLATION



CE MARKING

