

EDGE LIT



Construction	Tufted, Textured Loop Pile
Face Fibre	Milliken-Certified WearOn® Nylon Type 6,6
Soil Release	StainSmart®
Finished Face Weight	509 g/m ²
Gauge	1/12
Rows	38.6st/10cm
Tuft Density	182,100/m ²
Finished Pile Height	3.3 mm
Standard Backing	PVC-Free WellBAC™ Comfort Cushion Available with TractionBack® on request
Nominal Total Thickness	7.1 mm
Nominal Total Weight	3024 g/m ²
Plank Size	25 cm x 100 cm
Planks per Pallet	Minimum 25m ² / Maximum 99m ²
Tile Size	1000 cm x 1000 cm
Tiles per Pallet	Minimum 25m ² / Maximum 99m ²

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Cfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self extinguishing
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	30 dB
Sound Absorption (ISO354)	0.25 Class E
Alpha s values	125Hz 0.00, 250Hz 0.05, 500Hz 0.25, 1000Hz 0.25, 2000Hz 0.25, 4000Hz 0.35

ENVIRONMENTAL

39.3% recycled content by total product weight
EPD verified

WARRANTIES

12 year wear warranty
Lifetime Antistatic guarantee
Latent Defects guarantee

CERTIFICATIONS

INSTALLATION

Monolithic	Ashlar Random	Herringbone

CE MARKING

--	--	--	--	--	--	--