

MAJOR FREQUENCY

Distortion

Construction	Tufted, Textured Loop Pile
Face Fibre	Solution Dyed Nylon (20% recycled content)
Soil Release	StainSmart® for soil release, liquid repellence (on light colours LRV >20)
Finished Face Weight	560 g/m ²
Gauge	47.2 / 10 cm
Rows	37.5 / 10 cm
Tuft Density	177,200 /m ²
Finished Pile Height	2.9 mm
Standard Backing	Comfort Lite 90% recycled open cell polyurethane cushion backing Available with TractionBack® on request
Nominal Total Thickness	8.9 mm
Plank Size	25 cm x 100 cm
Nominal Total Weight	4000g/m ²
Planks per Box	11 (2.75m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	31 dB
Sound Absorption (ISO354)	0.30 Class D
Alpha s values	125Hz 0.05, 250Hz 0.05, 500Hz 0.30, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.35

ENVIRONMENTAL

59% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

TUV & CRI Green Label Plus certified for indoor air quality

EPD verified

WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICACIONES

INSTALLATION

Ashlar Random	Herringbone

CE MARKING

13 DOP-0338-100402 EN 14041:2018						