

NORTHWARD BOUND

Glacier / Ice / Snow

| | |
|-------------------------|---|
| Construction | Tufted, Textured Loop Pile |
| Face Fibre | Solution Dyed 100% Nylon |
| Soil Release | StainSmart® for soil release, liquid repellence - selected colours only (on light colours LRV >20) |
| Finished Face Weight | 500 g/m ² |
| Gauge | 47.2 / 10 cm |
| Rows | 37.5 / 10 cm |
| Tuft Density | 177,000 /m ² |
| Finished Pile Height | 2.8 mm |
| Standard Backing | Comfort Lite 90% recycled open cell polyurethane cushion backing Available with TractionBack® on request |
| Nominal Total Thickness | 9.2 mm |
| Tile Size | 50 cm x 50 cm |
| Nominal Total Weight | 4000 g/m ² |
| Tiles per Box | 22 (5.5m ²) |

PERFORMANCE

| | |
|--|---|
| Flammability (Euroclassification EN13501:1-2002) | Class Bfl - s1 |
| Flammability (Radiant Panel ASTM-E-648) | Class 1 |
| Flammability (Hot Metal Nut BS4790) | Low Radius of Char |
| Use Classification (EN 1307) | Class 33 Heavy Commercial Use |
| Castor Chair (BS EN 985:2001) | Class A - Intensive use (r value ≥ 2.4) |
| Static Electricity (ISO 6356) | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3) | 31 dB |
| Sound Absorption (ISO354) | 0.30 Class D |
| Alpha s values | 125Hz 0.00, 250Hz 0.05, 500Hz 0.35, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.35 |

ENVIRONMENTAL

59% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

TUV & CRI Green Label Plus certified for indoor air quality

EPD verified

WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

*StainSmart® Applied to the following colours only

Voyage, Discovery, Encounter

CERTIFICATIONS

| | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | |
| | | | | | | | | | | |

INSTALLATION



Monolithic

CE MARKING

| | | | | | | |
|--|--|--|--|--|--|--|
| | | | | | | |
|--|--|--|--|--|--|--|