

WIREFRAME

Wireframe / Wireframe Expressions

Construction	Tufted, Level Loop Pile
Face Fibre	100% Nylon
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	420 g/m ²
Gauge	39.4 / 10 cm
Rows	68 / 10 cm
Tuft Density	267,720 /m ²
Finished Pile Height	3.4 mm
Standard Backing	Comfort Lite 90% recycled open cell polyurethane cushion backing Available with TractionBack® on request
Nominal Total Thickness	8.6 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	3700 g/m ²
Tiles per Box	20 (5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value ≥ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	32 dB
Sound Absorption (ISO354)	0.30 Class D
Alpha s values	125Hz 0.02, 250Hz 0.04, 500Hz 0.38, 1000Hz 0.23, 2000Hz 0.28, 4000Hz 0.37

ENVIRONMENTAL

60% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

EPD, TUV certified

WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

INSTALLATION



Monolithique

CE MARKING

18
DOP-0338-100402
EN 14041:2004